



mec-pack line

Features

The Mec-Pack line offers many advantages that other brands do not: high quality construction, high volume, competitive pricing, motorized center seal – no handle adjustment required. The seal head automatically raises or lowers using a toggle switch. Using this standard feature will result in huge film savings. Easy product size changeover and straight-line product flow. The STA model includes a “kissing” conveyor for small products.



mec-pack sta

technical specifications

	std / sta
sealer power supply	220 V/3 PH – 20 AMPS
sealer air consumption	1 CFM @ 80 psi
minimum package dimensions	3.6" x 3.6"
maximum package dimensions	17.6" x 21.6"
maximum package height	6"
packaging speed	up to 40 packs/min.
minimum centerfold film width	8"
maximum centerfold film width	21.5"
motorized center seal	yes
kissing conveyor	sta only
overall sealer dimensions (W x L x H)	39" x 71" x 57"
sealer shipping weight	990 lbs.

WRAP SYSTEMS

AUTOMATIC SHRINK

mec-pack line



mec-pack sm

mec-pack big

technical specifications

	sm	big
sealer power supply	220 V/1 PH – 10 AMPS	220 V/3 PH – 10 AMPS
sealer air consumption	1 CFM @ 80 psi	1 CFM @ 80 psi
minimum package dimensions	2.3" x 2.3"	7.1" x 4"
maximum package dimensions	13.7" x 17.7"	29.5" x 24.5"
maximum package height	2"	6"
packaging speed	up to 40 packs/min.	up to 40 packs/min.
minimum centerfold film width	6"	10"
maximum centerfold film width	16"	27.5"
overall sealer dimensions (W x L x H)	29" x 52" x 52"	45" x 94" x 57"
motorized center seal	n/a	yes
kissing conveyor	n/a	n/a
shipping weight	450 lbs.	1100 lbs.

technical specifications subject to variations without prior notice



PRO PACK GROUP

196 Coolidge Ave., Englewood, NJ 07631 - Tel. 201-871-8787 - Fax 201-871-8908
www.dibipack.com - info@dibipack.com / www.shrinkfilm.com - info@shrinkfilm.com