

WRAP SYSTEMS



PRO PACK GROUP

PALLET

ecospir line

Features

Modern and innovative, each model is designed to maximize operating safety, up time, ease of use and wrapping performance.

option



platform
speed control

option



facilitated film hooking and
cutting patented device



elc/s

technical specifications

manual cycle	yes
automatic cycle	yes
load height sensing photo-cell	yes
programmable parameters	2
bottom wrap setting	yes
top wrap setting	yes
maximum pallet height	78 1/2"
turn-table diameter	59"
maximum pallet dimension	40" x 48"
maximum pallet weight	2200 lbs.
turn-table speed	8,5 rpm
turn-table height above floor	2.75"
maximum roll diameter	12"
roll width	20"
power supply	110 V – 15 AMPS
machine weight	575 lbs.
overall machine dimensions (W x L x H)	59" x 87" x 92"

technical specifications subject to variations without prior notice

WRAP SYSTEMS

PALLET

ecospir line

options



pneumatic top press



power stretch

option



facilitated film hooking and cutting patented device



a/id

technical specifications

manual/automatic cycle	yes
programmable parameters	5
programs	4
maximum pallet height	87"
turn-table diameter	59"
maximum pallet dimension	40" x 48"
maximum pallet weight	4000 lbs.
turn-table speed adjustable	up to 10 rpm
turn-table height above floor	2.75"
maximum roll diameter	12"
roll width	20"
power supply	220 V/3 PH V - 15 AMPS
air consumption (only with top press)	6 cf/cycle @ 80 psi
weight	950lbs.
overall machine dimensions (W x L x H)	59" x 96" x 100"

technical specifications subject to variations without prior notice



PRO PACK GROUP

196 Coolidge Ave., Englewood, NJ 07631 - Tel. 201-871-8787 - Fax 201-871-8908
www.dibipack.com - info@dibipack.com / www.shrinkfilm.com - info@shrinkfilm.com