

# DYNACLEAR

## HOT SLIP SHRINK FILM

### Optical and Mechanical Properties:

- ✚ High performance and productivity with outstanding yield
- ✚ Low temperatures and less energy with high shrinkage
- ✚ Fast sealing and hot tack
- ✚ Hot slip properties after shrinkage

### APPLICATIONS

- ✚ Unique technical properties allow Dynaclear HS to give excellent results from manual to automatic high speed machines.
- ✚ High degree of shrinkage, low shrink temperature, good optics and outstanding clarity: Dynaclear HS is very versatile and uniquely suited to a large variety of packaging systems and applications.

Code	Type	Thickness	Characteristics
HS	Hot slip	60/75	Multi-purpose film that shrinks at very low temperatures. HS also is High Shrink, shrinking up to 70% Particularly recommended for high speed FFS machines, multi-packing

#### Warranty

A limited warranty by Pro Pack Group covers each system for a period of one year. Specific details regarding this warranty are available from Pro Pack Group and its authorized distributors.

#### PRO PACK GROUP

196 Coolidge Avenue,  
Englewood, NJ 07631  
Ph. (201) 871-8787 – Fax (201) 871-8908  
[www.shrinkfilm.com](http://www.shrinkfilm.com)

#### Distributed by: